




BEAM CLAMP

The Beam Clamp is a structural attachment to the top or bottom of metal I-beams, purlins, channel, or angle iron. They are available for 3/8" and 1/2" threaded rod.

SMALL MOUTH BEAM CLAMP

FEATURES:

- Malleable iron
- Hardened steel cup point set screw
- Complies with:
 - Cast Clamps: Federal Specification A-A-1192A (Type 19) and Manufacturers' Standardization Society ANSI/SP-69 and SP58 (Type 19)
- Maximum Load Limits:
 - Small mouth 3/8 in: 400 lbs
 - Small mouth 1/2 in: 500 lbs
- Designed to provide attachment of various hanger rods to structural members without drilling or welding
- UL Listed and FM approved




Item #	Code	Description	Quantity
13179	BCSN38	3/8in Plated Small Mouth Cast Beam-Clamp w/ Lock Nut	100/box
13180	BCSN12	1/2in Plated Small Mouth Cast Beam-Clamp w/ Lock Nut	50/box

LARGE MOUTH BEAM CLAMP

FEATURES:

- Malleable iron
- Hardened steel cup point set screw & locking nut
- Complies with:
 - Cast Clamps: Federal Specification A-A-1192A (Type 19) and Manufacturers' Standardization Society ANSI/SP-69 and SP58 (Type 19)
- Maximum Load Limits:
 - Large mouth 3/8 in: 400lbs
- Designed to provide attachment of various hanger rods to structural members without drilling or welding
- UL Listed and FM approved



Item #	Code	Description	Quantity
13177	BCNL38	3/8in Plated Large Mouth Cast Beam Clamp w/ Lock Nut	50/box

Duro Dyne Corporate Headquarters, Bay Shore, NY
 631-249-9000 • Fax: 631-249-8346
 Duro Dyne Midwest • Duro Dyne West • Duro Dyne Canada
 www.durodyne.com • E-mail: durodyne@durodyne.com






BEAM CLAMP

The Beam Clamp is a structural attachment to the top or bottom of metal I-beams, purlins, channel, or angle iron.

C-CLAMP BEAM CLAMP

FEATURES:

- Carbon steel with hardened steel cup point set screw
- Complies with:
Stamped Clamps: Federal Specification A-A-1192A (Type 23) ANSI/SP-69 AND SP-58 (TYPE 23)
- Maximum Load Limits:
Steel C-Clamp 3/8 in: 400lbs
- Designed for attaching hanger rod to the bottom of a beam. The hanger rod should make contact with the beam flange to ensure full engagement.
- UL Listed and FM approved



Item #	Code	Description	Quantity
13184	CCN38	3/8in Plated Stamped C-Clamp w/ Lock Nut	100/box

Duro Dyne Corporate Headquarters, Bay Shore, NY
631-249-9000 • Fax: 631-249-8346
Duro Dyne Midwest • Duro Dyne West • Duro Dyne Canada
www.durodyne.com • E-mail: durodyne@durodyne.com



© Duro Dyne Corp.
Printed in USA 3/9/2020
BF013428